

MODEL 352 - 045 - XXX*

FIXED ATTENUATOR

Frequency Range: DC - 2.4 GHz

Impedance: 50 Ohms nominal

Attenuation Value: 3, 6, 10, 20, 30 dB available

Attenuation Accuracy:

	<u>3 dB</u>	<u>20 dB</u>
	DC - 1 GHz ± 0.5 dB	DC - 1 GHz ± 0.6 dB
	1 - 2.4 GHz - 0.5 dB / +1.0 dB	1 - 2.4 GHz - 0.5 dB / +1.5 dB
	<u>6 dB</u>	<u>30 dB</u>
	DC - 1 GHz ± 0.6 dB	DC - 1 GHz ± 1.0 dB
	1 - 2.4 GHz - 0.5 dB / +1.2 dB	1 - 2.4 GHz - 0.5 dB / +1.5 dB
	<u>10 dB</u>	
	DC - 1 GHz ± 0.6 dB	
	1 - 2.4 GHz - 0.5 dB / +1.5 dB	

VSWR: DC - 1 GHz 1.10:1 maximum
 1 - 2.4 GHz 1.25:1 maximum

Power Input: 1000 Watts average (uni - directional)

RF Connectors: N Female / Female

Operating Temperature: - 40°C to + 40°C

Outline Drawing: MED - 0063

* Insert desired attenuation value (example: 3 dB = 003)

ECF #	Date	Rev.
Issue	09/23/02	0

Approved By: Approved Internet/Email Copy