



Note: \* length shown for attenuation values 1 thru 12 dB, attenuation values 13 thru 30 dB have an overall length of 1.02

# BroadWave Technologies, Inc.

2 Watt Fixed Attenuator, SMA Male/Female

DWG. NO. <b>MED - 0461</b>	DATE <b>5-21-08</b>	SCALE <b>1 : 1</b>	REV. LEVEL <b>REV C</b>
-------------------------------	------------------------	-----------------------	----------------------------

ECN#	DONE BY	DATE	REV	APPROVALS	TOLERANCE CHART
0577	AK	2-27-08	A	Proprietary Information APPROVALS DATE <b>3-08-05</b>	Fractional Dimensions ± 1/64
0583	AK	3-3-08	B		Angular Dimensions ± 1/2 degree
0639	AK	5-21-08	C		2 Place Decimals
0859	CH	9-8-09	D		3 Place Decimals
				DRAWN BY <b>MCA</b>	DATE <b>3-08-05</b>
				APPROVED BY	FINISH
					<b>Passivated Stainless Steel</b>

TOLERANCE CHART	
Fractional Dimensions	± 1/64
Angular Dimensions	± 1/2 degree
MATERIAL SPECIFICATION INFORMATION	
MATERIAL TYPE	Passivated Stainless Steel